PRE-INSPECTION CHECKLIST

Doors and aisles are not obstructed No slide bolts, hasps, etc. on doors.
No slide bolts, hasps, etc. on doors.
Illuminated exit signs lit.
Emergency lighting operable
FIRE EXTINGUISHERS
As a minimum one 5 lb. ABC type extinguisher installed
Yearly service tag in date. One year cycle
Fire extinguisher hung up or in approved cabinet and not obstructed.
FIRE PROTECTION EQUIPMENT
Hood extinguishing system maintained, and six month service and hood cleaning documented.
Fire detection system tested annually and records kept.
Sprinkler system tested annually and records kept.
18 inch clearance around sprinkler heads.
Outside sprinkler connection maintained with proper signage.
ELECTRICAL
No extension cords used in place or permanent wiring.
No multi pug adapters in use, other than approved power strips.
30 inch clearance in front of circuit breaker box.
Cover plates on all outlets and switches.
FLAMMABLE, COMBUSTIBLE, COMPRESSED GASSES, LIQUIDS, ETC.
No propane stored inside any building.
All compressed gas cylinders chained securely to wall.
Flammable liquids stored properly in approved containers and cabinets.
GENERAL
36 inch clearance around heaters.
Fire lanes marked out and maintained if required.
Note: This is a list of the most common violations that can be readily identified by the occupant.

PLACES OF ASSEMBLY PRE-INSPECTION CHECKLIST

EXITS							
Doors and aisles a	Doors and aisles are not obstructed						
	hardware installed on exit doors.						
No slide bolts, has							
Illuminated exit s							
Emergency lighting							
FIRE EXTINGUISHERS							
Yearly service tag	in date. One year cycle						
	nung up or in approved cabinet and not obstructed.						
FIRE PROTECTION EQ							
Hood extinguishing documented.	g system maintained, and six month service and hood cleaning						
	om tostad annually and records kent						
Comincial an aviation to	em tested annually and records kept.						
19 inch clearance	ested annually and records kept.						
18 inch clearance a							
Outside sprinkler c	connection maintained with proper signage.						
ELECTRICAL							
No extension core	ds used in place or permanent wiring.						
No multi pug adar	pters in use, other than approved power strips.						
30 inch clearance	e in front of circuit breaker box.						
Cover plates on al	l outlets and switches.						
	STIBLE, COMPRESSED GASSES, LIQUIDS, ETC.						
No propane store	ed inside any building.						
Patio type heater	s prohibited.						
All compressed gas	s cylinders chained securely to wall.						
Flammable liquids	stored properly in approved containers and cabinets.						
GENERAL							
36 inch clearance a	around heaters.						
	out and maintained if required.						
Note: This is a list of the me	ost common violations that can be readily identified by the						

Note: This is a list of the most common violations that can be readily identified by the occupant.